



26ET- TRADITIONAL SERIES EMBEDDED WASHINGTON POLE

POLE DESIGNATION	POLE HEIGHT ABOVE GROUND	EM-BEDDED DEPTH	OVER-ALL LENGTH	BUTT DIA.	ULTIMATE G.L. MOMENT (ft.-lbs.)	WEIGHT (lbs.)
26ET-12	12'-0"	4'-0"	16'-0"	21"	7,500	740

() POLES REQD, EACH WITH A5 TENON (3" O.D. x 3" L.; SEE P/N# 4007SEPA).

- NOTES:
- FIL MIX (12I): BLACK/BLACK, EXPOSED AGGREGATE FINISH, WITH AMERSHIELD ANTI-GRAFFITI COATING.
 - ASTM C-150 TYPE III GRAY CEMENT.
 - f_c @ 28 DAYS = 6,000 PSI, USING SPUN CYLINDER TEST (MIN.).
 - f_c @ 28 DAYS = 5,000 PSI, USING ASTM C-31 CYLINDER TEST.
 - POLES MANUFACTURED PER ASTM C1089-97 SPECIFICATIONS.
 - PROTECTIVE COAT EXPOSED P.C. WIRES AT POLE ENDS.
 - FIL MFG: PRESTRESSED WITH (4) 5/16" DIA. A-416 PRESTRESS CABLES (7-STRAND).
 - MOD 38: (4) 3/8"-16UNC TOP MT CPLNGS/ANCHORS ON A 3-1/2" B.C.
 - ALL EXPOSED METAL PAINTED SEMI-GLOSS BLACK (PA).

Ameron POLE PRODUCTS & SYSTEMS				
BONNEY LAKE- WA 26ET-12 POLE WITH TENON				
<small>THIS DOCUMENT CONTAINS INFORMATION WHICH IS PROPRIETARY TO AMERON. IT SHALL NOT BE REPRODUCED, USED OR DISCLOSED TO ANYONE WITHOUT THE PRIOR WRITTEN PERMISSION OF AMERON.</small>				
DRAWN: J.C.	5/05	SCALE N.T.S.	DWG. NO. SK053505	REV A
CHK'D:				

Approved:  March 16, 2018
 City Engineer Date
STREET STANDARD DETAIL



Dwg No: **S16**
26ET-12 POLE WITH TENON